

IN THE CLAIMS:

Please cancel claim 6 without prejudice or disclaimer.

Please amend claim 1 as follows:

Claim 1 (Currently Amended): Pressure-air driven percussion device for a down-the-hole drill, the pressure-air driven percussion device comprising

a hammer-piston axially reciprocally movable in a hammer-piston chamber through a driving device, said hammer-piston in operation acting with a hammer-end against an upper end of a drill bit positioned inside a chuck,

an air cushion for reducing percussive power, said air cushion being arranged at the hammer-end of the hammer-piston in positions where the drill bit has been moved past a predetermined distance in a percussion direction,

the drill bit being sealingly slidingly supported in a drill bit bushing, and

the hammer-end of the hammer-piston sealingly cooperating with the drill bit bushing in said positions to form said air-cushion,

said air-cushion ~~being formed in a~~ forming a sealed air volume defined by vertically between an upper end of the drill bit, ~~the drill bit bushing~~ and the hammer-end of the hammer-piston and laterally by the drill bit bushing.

Claim 2 (Previously Presented): Percussion device according to claim 1, wherein an upper end portion of the drill bit is sealingly, slidingly supported in the drill bit bushing.

Claim 3 (Cancelled).

Claim 4 (Previously Presented): Percussion device according to claim 1, wherein the drill bit bushing is arranged to be supported by a housing of the down-the-hole drill.

Claim 5 (Previously Presented): Percussion device according to claim 1, wherein the hammer-piston chamber is formed by a housing of the down-the-hole drill.

Claim 6 (Previously Presented): Percussion device according to claim 1, wherein the driving device includes a leakage passage for pressure-air through which a flushing position is established, and the pressure-air is allowed to leak past the driving device in advanced positions in the percussion direction of the hammer-piston.

Claim 7 (Previously Presented): Percussion device according to claim 1, wherein the hammer-piston is provided with a central axial channel which continues in the drill

bit over a foot valve, which is fastened in the drill bit and seals against the hammer-piston.

Claim 8 (Previously Presented): Percussion device according to claim 7, wherein the air-cushion is limited by an outside surface of the foot valve.

Claim 9 (Currently Amended): Down-the-hole drill comprising

a percussion device with a hammer-piston axially reciprocally movable in a hammer-piston chamber through a driving device, said hammer-piston in operation acting with a hammer-end against an upper end of a drill bit positioned inside a chuck,

an air cushion for reducing percussive power arranged at the hammer-end of the hammer-piston in positions where the drill bit has been moved past a predetermined distance in a percussion direction,

the drill bit being sealingly slidably supported in a drill bit bushing, and

the hammer-end of the hammer-piston sealingly cooperating with the drill bit bushing in said positions to form said air-cushion,

said air-cushion being arranged ~~to be formed~~ in a sealed air volume defined by vertically between an upper end of the drill bit, ~~the drill bit bushing~~ and the hammer-end of the hammer-piston and laterally by the drill bit bushing.